

Charts 2013 EM, Construction equipments, Wheelloaders,



Tire / Rim Size	Filling Amount		Tire / Rim Size	Filling Amount		Tire / Rim Size	Filling Amount	
	Liter	strokes		Liter	strokes		Liter	strokes
15 Zoll			24 Zoll			28 Zoll		
7,00	0,75	6	11.00	1,78	14	16.9 R	3,8	30
7.50 R	0,80	6,4	11,20	2,00	16	19.5 LR	4,8	38
8.25 R	0,87	6,96	12.00	2,00	16	29 Zoll		
10 R	1,25	10	13.00	2,30	18	26.5 R	7,5	60
27x8.50 R	0,87	6,96	14.00 + R	2,75	22	29.5 R	9,0	72
14.5 R	2,25	18	14,90 R	3,00	24	30 / 65 R	8,0	64
225 / 75 R	1,00	8	15.00 R	3,15	25	33.25 R	10,5	84
350 / 65	1,45	12	16.00 + R	3,38	27	775 / 65 R	8,25	66
400 / 80	2,45	20	16,9	3,38	27	800 / 65 R	9,0	72
16 Zoll			17,5	3,75	30	875 / 65 R	10,0	80
11. LR	1,45	12	19,5	4,38	35	30 Zoll		
16.5 Zoll			20	4,50	36	16.9 R	3,6	29
10 R	1,25	10	385 / 95 R	3,50	28	18.4 R	4,5	36
12 R	1,75	14	440-455 / 70 R	3,38	27	33 Zoll		
18 Zoll			495 / 70 R	4,00	32	18.00+ R	5,25	42
10,5	1,38	11	555 / 70 R	5,00	40	33.5 R	11,5	92
12,0	1,88	15	25 Zoll			35/65 R	11,0	88
12,5 / 80R	1,70	14	12.00	2,25	18	37.5 R	13,0	104
275 / 80 R	1,75	14	13.00	2,50	20	34 Zoll		
365 / 70 R	2,15	17	14.00 + R	2,78	22	18.4 R	4,5	36
405 / 70 R	2,50	20	15.5 + R	3,00	24	35 Zoll		
19,5 Zoll			16.00 + R	3,50	28	21.00 R	6,0	48
245 / 70 R	1,25	10	17.5 + R	4,00	32	24.00 R	7,0	56
265 / 70 R	1,38	11	18.00 + R	4,25	34	29.5 R	9,5	76
285 / 70 R	1,50	12	20.5 + R	4,50	36	33.25 R	11,5	92
20 Zoll			21.00	5,00	40	37.25 R	13,5	108
7.00	0,85	7	23.5 + R	6,00	48	39 Zoll		
7.50	0,95	8	26.5 R	7,00	56	37.5 R	14,5	116
8.25	1,10	9	29.5 R	9,00	72	40 / 65 R	13,0	104
9.00	1,20	10	25/65 R	5,50	44	41.25 / 70	15,5	124
10.00	1,50	12	30 / 65 R	7,50	60	40.5 / 75 R	15,5	124
10,5 R 275 / 80	1,65	13	385 / 95 R	3,50	28	45 / 65	17,0	136
11 / 80	1,65	13	395 / 80 R	3,50	28	45 Zoll		
12.00	1,85	15	445 / 80 R	3,50	28	45 / 65 R	11,5	92
12,5 R	1,88	15	445 / 95 R	4,00	32	49 Zoll		
14.00	2,38	19	525 / 80 R	4,50	36	24.00 R	9,0	72
14,5 R	2,50	20	550 / 65 R	4,50	36	27.00 R	10,0	80
16.00 R 425 / 95	2,88	23	550 / 70 R	4,75	38	51 Zoll		
16 / 70 400 / 70	2,75	22	600 / 65 R	5,25	42	30.00	12,0	96
365 / 80 R	2,50	20	605 / 80 R	6,00	48	33.00	14,0	112
405 / 70 R	2,75	22	625 / 70 R	5,75	46	36.00	16,0	128
425 / 75 R	3,00	24	650 / 65 R	6,00	48	56,5 Zoll		
22,5 Zoll			685 / 80 R	7,13	57	27 R	11,0	88
15 R	2,75	22	705 / 70 R	7,00	56	57 Zoll		
18 R	3,40	27	750 / 65 R	7,25	58	37.00 R	19,0	152
24 Zoll			755 / 70 R	8,00	64	40.00	20,0	160
10.00	1,75	14	850 / 65 R	9,00	72	50 / 80 R	27,0	216

Products: AirSeal **HD** or AirSeal **HD Spezial**

1 notch = 30 ml= 1 US fl.Ounce

For use in heavy terrain, waste depots etc. increase filling amount up to 100 %

Pump # 405 full downstroke 1/3 Liter, = 0,125 L, so are 8 stroke 1 Liter